

**beyma** //

PROFESSIONAL LOUDSPEAKERS

CEILING LOUDSPEAKER  
5T/6T/8T**TECHNICAL SPECIFICATIONS**

<b>Type</b>	2 way coaxial loudspeaker
<b>Nominal diameter</b>	<b>8T</b> 200 mm. 8 in. <b>6T</b> 165 mm. 6.5 in. <b>5T</b> 125 mm. 5 in.
<b>Rated impedance</b>	8 ohms.
<b>Power capacity</b>	
<b>8T</b>	55 w RMS (8 ohms.) 1.5 / 2.5 / 5 / 10 w (100 v)
<b>6T</b>	45 w RMS (8 ohms.) 1.5 / 2.5 / 5 / 10 w (100 v)
<b>5T</b>	30 w RMS (8 ohms.) 1.5 / 3 / 6 (100 v)
<b>Sensitivity</b>	<b>8T</b> 91dB, <b>6T</b> 90dB, <b>5T</b> 89dB, 1w @ 1m
<b>Frequency range</b>	<b>8T</b> 40-20000 Hz <b>6T</b> 45-20000 Hz <b>5T</b> 55-20000 Hz
<b>Dispersion angle</b>	90°
<b>Transformer line</b>	100 v

**KEY FEATURES**

- 2 way coaxial loudspeaker
- Built-in 100V transformer with 8 ohms option
- 4 individual power settings in 100V mode
- 90° dispersion angle
- White ABS back cover
- Easy to install
- Designed for public address ceiling applications

**HALL SIZE**

<b>8T</b>	255 mm
<b>6T</b>	210 mm
<b>5T</b>	180 mm

**MATERIALS**

- **LF unit diaphragm:** propylene.
- **HF unit diaphragm:** polycarbonate.
- **Grid:** metal.
- **Back cover:** ABS.